

What is claimed is:

- 5 1. A device comprising:
- a communication system transmitter for transmitting signals via a radio interface in a first frequency band;
 - 10 - a receiver for receiving signals via a radio interface in a second frequency band, said receiver including an attenuation component for attenuating signals received by said receiver; and
 - a controlling portion setting an attenuation which is applied by said attenuating component to
15 signals received by said receiver to a higher value in case said communication system transmitter is transmitting signals with a power level exceeding a certain value, and setting an attenuation which is applied by said attenuating
20 component to signals received by said receiver to a lower value in case no signal is transmitted by said communication system transmitter, wherein said higher value is sufficiently high to prevent an evaluation of said attenuated received signals,
25 when said attenuation is set to said higher value.
2. The device according to claim 1, wherein said communication system transmitter includes a variable amplifier for amplifying signals which are to be
30 transmitted by said communication system transmitter, and wherein said controlling portion sets said attenuation which is applied by said attenuating component to signals received by said receiver to a

value which increases with an increasing amplification factor of an amplification applied by said variable amplifier to signals which are to be transmitted by said communication system transmitter.

5

3. The device according to claim 1, wherein said device comprises a communication system section including said communication system transmitter and a receiver section including said receiver receiving signals in a second frequency band, and wherein said controlling portion is located in at least one of said communication system section and said receiver section.

10

4. The device according to claim 3, wherein said controlling portion includes at least a part of a processor provided in said communication system section and at least a part of a processor provided in said receiver section.

20

5. The device according to claim 1, wherein said receiver receiving signals in said second frequency band further includes an automatic gain control component, and wherein said controlling portion combines information from said automatic gain control component and information from a communication system section including said communication system transmitter for determining an attenuation to be set.

25

6. The device according to claim 1, wherein said controlling portion determines an attenuation to be set based on at least one of the power level of signals transmitted by said communication system

30

transmitter and the power level of signals received by said receiver receiving signals in said second frequency band.

- 5 7. The device according to claim 1, further comprising a communication system receiver for receiving signals in said first frequency band, wherein said controlling portion determines an attenuation to be set based on the power level of signals received by
10 said communication system receiver.
8. The device according to claim 7, wherein said controlling portion determines an attenuation to be set based in addition on the power level of signals
15 received by said receiver receiving signal in said second frequency band.
9. The device according to claim 1, wherein said attenuating component comprises a variable gain
20 attenuator, and wherein said variable gain attenuator applies at least part of said set attenuation to a signal received by said receiver by varying an attenuation applied by said variable gain attenuator to said received signal.
- 25 10. The device according to claim 9, wherein said receiver receiving signals in said second frequency band further includes an amplifier for amplifying signals received via an antenna of said device, and a
30 processing portion for processing signals amplified by said amplifier, and wherein said variable gain attenuator is arranged between said amplifier and said processing portion.

11. The device according to claim 1, wherein said
attenuating component is integrated with at least one
other component of said receiver receiving signals in
5 said second frequency band in an integrated circuit.
12. The device according to claim 1, wherein said
attenuating component is implemented in a dedicated
integrated circuit, which dedicated integrated
10 circuit is external to other components of said
receiver receiving signals in said second frequency
band.
13. The device according to claim 1, wherein said
15 attenuating component comprises a variable amplifier,
wherein said variable amplifier applies at least part
of said set attenuation to a signal received by said
receiver by varying an amplification factor of an
amplification applied by said variable amplifier to
20 said received signal.
14. The device according to claim 1, further comprising
an antenna which is connected to said receiver
receiving signals in said second frequency band,
25 wherein said attenuating component comprises a
component applying at least part of said set
attenuation to a signal received by said receiver by
detuning said antenna.
- 30 15. The device according to claim 1, wherein said
attenuating component comprises a component applying
at least part of said set attenuation to a signal
received by said receiver receiving signals in said

second frequency band by reducing at least for one component of said receiver a supplied operation voltage.

- 5 16. The device according to claim 1, wherein said receiver receiving signals in said second frequency band further includes a first converting component for converting a received radio frequency signal into an intermediate frequency signal and a second
10 converting component for converting an intermediate frequency signal output by said first converting component into a baseband signal, and wherein said attenuating component applies said set attenuation to a signal received by said receiver at least at one of
15 a radio frequency, an intermediate frequency and a baseband frequency.
17. The device according to claim 1, further comprising evaluating means adapted to evaluate said attenuated
20 received signals only in case said attenuated received signals have a sufficiently high power level.
18. A component comprising: a controlling portion setting
25 an attenuation which is applied by an attenuating component of a receiver of a communication system to signals received by a radio interface of said receiver in a second frequency band to a higher value in case a transmitter of said communication system is
30 transmitting signals via a radio interface in a first frequency band with a power level exceeding a certain value, and setting an attenuation which is applied by said attenuating component to signals received by

said receiver to a lower value in case no signal is transmitted by said communication system transmitter, wherein said higher value is sufficiently high to prevent an evaluation of said attenuated received signals, when said attenuation is set to said higher value.

19. A method for improving the performance of a receiver via a comprising:
- attenuating a signal received by said receiver via a radio interface in a second frequency band with a higher attenuation, in case a communication system transmitter in which said receiver is combined in a single device is transmitting signals via a radio interface in a first frequency band with a power level exceeding a certain value, and
- attenuating a signal received by said receiver with a lower attenuation, in case no signal is transmitted by said communication system transmitter, wherein said higher attenuation is sufficiently high to prevent an evaluation of received signals attenuated with said higher attenuation.
20. The method according to claim 19, wherein said communication system transmitter amplifies signals for transmission with a variable amplification factor, and wherein signals received by said receiver receiving signals in said second frequency band are attenuated with an attenuation which is increased with an increasing amplification factor used by said communication system transmitter for amplifying signals for transmission.

21. The method according to claim 19, wherein for
determining an attenuation to be used, information
provided by an automatic gain control for said
receiver and information provided by a communication
5 system section including said communication system
transmitter is combined.
22. The method according to claim 19, wherein an
attenuation to be used is determined based on at
10 least one of the power level of signals transmitted
by said communication system transmitter and the
power level of signals received by said receiver
receiving signals in said second frequency band.
- 15 23. The method according to claim 19, wherein an
attenuation to be used is determined based on the
power level of signals received by a communication
system receiver of said device in said first
frequency band.
- 20 24. The method according to claim 23, wherein an
attenuation to be used is determined based in
addition on the power level of signals received by
said receiver receiving signal in said second
25 frequency band.
25. The method according to claim 19, wherein signals
received by said receiver receiving signals in said
second frequency band are attenuated by an
30 attenuation applied by a variable gain attenuator.
26. The method according to claim 19, wherein signals
received by said receiver receiving signals in said

second frequency band are attenuated by reducing an amplification applied to said signals.

27. The method according to claim 19, wherein signals
5 received by said receiver receiving signals in said second frequency band are attenuated by detuning an antenna forwarding signals to said receiver.
28. The method according to claim 19, wherein signals
10 received by said receiver receiving signals in said second frequency band are attenuated by reducing at least for one component of said receiver a supplied operation voltage.
- 15 29. The method according to claim 19, wherein signals received by said receiver receiving signals in said second frequency band are attenuated at least at one of a radio frequency, an intermediate frequency and a
20 baseband frequency.
30. The method according to claim 19, further comprising evaluating said attenuated received signals only in case said attenuated received signals have a sufficiently high power level.
25
31. A device comprising:
- means for transmitting signals via a radio interface in a first frequency band;
 - means for receiving signals via a radio interface
30 in a second frequency band, said means for receiving including means for attenuating signals received by said means for receiving; and

- means for setting an attenuation which is applied by said means for attenuating to signals received by said means for receiving to a higher value in case said means for transmitting is transmitting signals with a power level exceeding a certain value, and setting an attenuation which is applied by said means for attenuating to signals received by said means for receiving to a lower value in case no signal is transmitted by said means for transmitting, wherein said higher value is sufficiently high to prevent an evaluation of said attenuated received signals, when said attenuation is set to said higher value.